

## **FEATURES**

- · Optional add-on heatsink to freely install based on ones preference
- Modern yet powerful aluminum heatsink for up to 10% temperature reduction
- Utilizes the PCI Express® Gen4 x4 interface supported by NVMe  $^{\text{TM}}$  1.4
- · Supports AES 256-bit Hardware-based Encryption to ensure superior data security
- Intelligent SLC caching algorithm and HMB technology (Host Memory Buffer) for high endurance and performance improvement
- Powerful Hardware LDPC ECC Engine for endurance and retention improvement
- · End to end data path protection with CRC parity
- SRAM error handling on major memory buffers
- · Supports Global Wear Leveling for SSD lifespan extension
- Thermal throttling algorithm to protect the SSD integrity
- Self-Monitoring, Analysis, and Reporting Technology (S.M.A.R.T.)

## **SPECIFICATIONS**

	N. 44 POL O . 4 4	
Host Interface	NVMe PCIe Gen4x4	
Form Factor	M.2 2280	
Capacity	500GB, 1TB, 2TB, 4TB	
Flash	strictly-selected 3D TLC NAND Flash	
Discoursian (La Marth)	80 x 22 x 3.4 mm (with heatsink)	
Dimension(LxWxH)	80 x 22 x 2.15 mm (without heatsink)	
Walak	10g (with heatsink)	
Weight	7g (without heatsink)	
Warranty	5-year limited warranty	

## **PERFORMANCE**

	500GB	1TB	2TB	4TB
Sequential Read up to (MB/s)	5000	5000	5200	5200
Sequential Write up to (MB/s)	3700	4800	4800	4800
4K Random Read up to (IOPS)	545K	620K	560K	540K
4K Random Write up to (IOPS)	510K	615K	615K	600K
Endurance (TBW)	350	700	1400	2800

\*Performance may vary based on different hardware test platforms, software, operating systems, etc.

## ORDERING INFORMATION

Capacity	Product Number	EAN Code
500GB	K500GM2SP0-C91	4895194901600
1TB	K01TBM2SP0-C91	4895194901617
2TB	K02TBM2SP0-C91	4895194901716
4TB	K04TBM2SP0-C91	4895194901723







